Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	UMAGE
--------------------------------	-------

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2329 (down-light-source)

I V DC OI IISIIL JOUI CC	Type	of lig	tht s	ource:
--------------------------	------	--------	-------	--------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Custom LED PCB 37,8V DC 700mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded st integer	27	Energy efficiency class	D
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	4 222 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pressed in W	oower (P _{on}),	26,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85
Outer	Height	580	Spectral power	See image
dimensions	Width	580	distribution in the	in last page
				Seite 1 / 3

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	1	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity	0,433
			coordinates (x and y)	0,396
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	18	Survival factor	0,90
the lumen main	tenance factor	0,96		

(a)_{'-'}: not applicable;

(b)_{'-'} : not applicable;

